

7/19/1

DIALOG(R)File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

07359511 **Image available**
SEAL RING

PUB. NO.: 2002-228008 [JP 2002228008 A]
PUBLISHED: August 14, 2002 (20020814)
INVENTOR(s): FUJIWARA HIDEKI
 ICHIHARA TAKAHIRO
APPLICANT(s): KOYO SEIKO CO LTD
APPL. NO.: 2001-025386 [JP 20011025386]
FILED: February 01, 2001 (20010201)
INTL CLASS: F16J-015/32

ABSTRACT

PROBLEM TO BE SOLVED: To provide a seal ring that prevents deterioration in sealing function of the seal ring caused by centrifugal force generated accompanying the outer cylinder rotation.

SOLUTION: The seal ring 7 partitions in an axial direction an annular space between a **shaft** body 2 and the outer cylinder 1 concentrically and rotatably disposed on an outer diameter side of the **shaft** body 2. The seal ring 7 has: an annular body 71 of which outer periphery is attached to the outer cylinder and of which inner periphery extends toward an outer peripheral **face** of the **shaft** body 2; and **radial lip** 72 that is formed of flexible elastic material, disposed to the inner periphery of the annular body 71 so as to project obliquely inward in a diameter direction, and is brought into press-contact with the outer peripheral **face** of the **shaft** body 2 with a required interference. The center of gravity R of a section with respect to a rocking fulcrum Q of the **radial lip** 72 is located at a position for preventing bending of the **radial lip** 72 outward in the diameter direction when receiving the rotational centrifugal force.

COPYRIGHT: (C)2002,JPO

C:\Program Files\Dialog\DialogLink\Graphics\37.bmp

